

**FILTRE INOX A CARTOUCHES**  
**- STAINLESS STEEL Filter Housing -**



Les Corps de Filtres, sont disponibles dans 4 versions avec les caractéristiques suivantes :

Tête en Inox 316L avec 2 prises manomètres 1/8", cuve en inox 316L electropolé, avec vis de purge 1/2"

Fermeture par étrier en inox 316L.

Raccordement 3/4" ou 1" BSP Femelle Cuve pour cartouches INOX 316L 9" 3/4 10" & 20", suivant les débits à Traiter.

Tirant en de fixation en Inox 316L ;

The Stainless Steel filter housings series are available in 4 Sizes with the following Characteristics:

316L STAINLESS STEEL Head with 2 vent plug 1/8",  
316L SS Sump electropolished with 1/2" drain.

316L SS Clamp systems for closure

Female BSP connectors from 3/4 " or 1"

Sumps are designed for 9" 3/4, 10" and 20" Cartridges.

SS tie beam to mount the cartridge

Flow rate from 2,5 up to 5m3/h

Max. Pressure: 15 bars (210 psi)

Max. Temp. : 90°C (195°F)

Ref.	Produit	E/S	Cuve	Dimensions L	mm H	Débit L/H
Part Number	Product	I/O	Smp	Size L	mm H	Flow Rate L/H
DB4000	DUB2i	3/4"	10"	134	320	2 500
DB4100	DUB2i	3/4"	20"	134	585	3 500
DB4200	DUB2i	1"	10"	134	320	3 900
DB4300	DUB2i	1"	20"	134	585	5 000

**Cartouches INOX 316L – 316 STAINLESS STEEL CARTRIDGES**

Ref.	Produit	Pour Corps de Filtre	Dimensions Ø	mm H	Microns
Part Number	Product	For Housing	Size Ø	mm H	Microns
4090560	X : 9" 3/4	3/4", 1", standard	70	248	60
4081560	XM : 8	3/4", 1", standard	70	225	60
4190560	XM : 19	3/4", 1", standard	70	470	60
4101560	XSM : 10	1 1/4", 1 1/2", 2"	70	220	60
4201560	XSM : 20	1 1/4", 1 1/2", 2"	70	470	60
4092560	X P: 9" 3/4	3/4", 1", standard	70	248	60
4202560	X P: 20"	3/4", 1", standard	70	508	60

**X = Cartouche lisse / Smooth Cartridge**

**XM = Cartouche Lisse avec Ressort de Compensation  
Smooth Cartridge with spiral spring**

**XSM = Cartouche Lisse avec Ressort de Compensation  
Smooth Cartridge with spiral spring**

**XP = Cartouche Plissé  
Pleated Cartridge**

